

MPC-Support channels







sendzimir galvanised

Field of application

- Ideal for pipe installation as support structure for air ducts in dry interiors
- Variety of mounting options for pre-wall installations and shelves in combination with extensive range of system components

Advantages

- Quick and efficient attachment of pipe sections and multiple pipe-ways
- Scale marks sideways and on the side with the slot simplify the alignment of the attachment elements during installation and facilitate the measuring and cutting to length of the section on site
- For secure fixing that is adjustable laterally and vertically
- High bending stiffness due to the cross-section design
- For setting up structures with correctly measured static loads by means of diverse connection components
- Suitable vibration control elements for all support channels available
- Clean-cut appearance by the use of MPC-protection caps
- Support channels 38/40 and 40/60 are awarded the RAL-quality mark of the „Gütegemeinschaft Rohrbe-festigung“



Profile 38/40



Profile 39/52



Profile 40/60

Features



Profile	Length [mm]	Part no.	Sales unit	Pack unit
38/40	2,000	129917	5	pieces
	3,040	129945	4	
	4,000	129964	1	
	6,000	130011		
39/52		130015		
40/60	2,000	129921		
	3,040	129946		
	4,000	129965		
	6,000	130020		



For use in areas with requirements on the duration of fire resistance, the boundary conditions set out in the fire test report must be observed.