



- **APPLICATION:**
For fixing elements in all type of installations:
Electrical, air conditioning, etc.
- **SPECIFICATIONS:**
High thermal resistance (-40 to +85 grades).
Self extinguishing as per UL 94 V2. based on UL-62275
Tension certificate as per TÜV & DNV-GL EN (IEC) 62275:2015.
Black colour has higher resistance to UV.
Round corners for installation safety.
- **MATERIAL:**
Manufactured in Polyamid 6.6 (Nylon).

TECHNICAL DATA

COD	COD		Unid. 	Unid. 	Ø Min.	Ø Max.	
20102	21102	100 x 2,5	100	50.000	3 mm.	20.5 mm.	8
20103	21103	130 x 2,5	100	25.000	3 mm.	30 mm.	8
20105	21105	200 x 2,5	100	25.000	3 mm.	52.5 mm.	8
20106	21106	140 x 3,6	100	25.000	3.5 mm.	33 mm.	18
20107	21107	200 x 3,6	100	20.000	3.5 mm.	52.5 mm.	18
20108	21108	300 x 3,6	100	10.000	3.5 mm.	84 mm.	18
20110	21110	160 x 4,6	100	10.000	3.5 mm.	36.6 mm.	23
20113	21113	200 x 4,8	100	10.000	3.5 mm.	49.5 mm.	23
20114	21114	250 x 4,8	100	10.000	3.5 mm.	65 mm.	23
20115	21115	300 x 4,8	100	10.000	3.5 mm.	81 mm.	23
20116	21116	360 x 4,8	100	5.000	3.5 mm.	100 mm.	23
20117	21117	430 x 4,8	100	5.000	3.5 mm.	122.5 mm.	23
20121	21121	300 x 7,6	100	5.000	8.5 mm.	82.8 mm.	54
20122	21122	365 x 7,6	100	2.500	8.5 mm.	103.5 mm.	54
20124	21124	550 x 7,6	100	1.000	8.5 mm.	162.5 mm.	54
20125	21125	780 x 8.8	100	1.000	8.5 mm.	235.5 mm.	80
20131	21131	1.000 x 12.4	100	1.000	18 mm.	315 mm.	120

