

Direct fastening system
for concrete and steel SC40II

RAWLPLUG®

Direct fastening system
for concrete and steel SC40II

RAWLPLUG®

RAWLPLUG OFFER ✓

Product code	Product	Product code	Range of nails		Magazine capacity	Battery charge	Shots per charge		
			mm	Fuel cell type					
R-RAWL-SC40 II		R-RAWL-SC40II	15-40	GP5	30	0.5	8000		
R-KNC, R-KSC		Product code		Pin diameter	Pin length	Pins quantity on plastic collation	Quantity per box	Fuel cells per box	
				mm	mm	pcs	pcs	pcs	
		R-KNC Plastic collated pins for steel or concrete							
		R-KNC-6/22/500	2.7	22	10	500	GP5		
		R-KNC-6/25/500	2.7	25	10	500	GP5		
		R-KNC-6/27/500	2.7	27	10	500	GP5		
		R-KNC-6/32/500	2.7	32	10	500	GP5		
		R-KNC-6/38/500	2.7	38	10	500	GP5		
		R-KSC Plastic collated pins for steel							
		R-KSC-6/17/500	2.7	17	10	500	GP5		
R-KSC-6/19/500	2.7	19	10	500	GP5				
R-RAWL-GP5		Product code	Type	Temp. range	Performance				
		R-RAWL-GP5	Propan, Butan	-5 - 35 °C	min. 500 mocowań	shots			
R-SC40-MCD		Product code	Dimensions	Quantity per box					
			mm	pcs					
R-SC40-MCS		R-SC40-MCD-6	Ø 6	100					
		R-SC40-MCD-8	Ø 8	100					
		R-SC40-MCD-10	Ø 10	100					
R-SC40-MCS		R-SC40-MCS-6	Ø 6	50					
		R-SC40-MCS-8	Ø 8	50					
		R-SC40-MCS-10	Ø 10	50					
R-SC40-MCS		R-SC40-MCS-12	Ø 12	100					
R-SC40-MW-25		R-SC40-MW-25	25	200					


Product code	Product	Product code	Fastener element	Quantity per box
R-SC40-HEX		R-SC40-HEX	6 self-locking straps	100
R-SC40-PCR		R-SC40-PCR-18	Ø 15-18	60
		R-SC40-PCR-25	Ø 20-25	40
		R-SC40-PCR-32	Ø 26-32	25
		R-SC40-PCR-42	Ø 35-42	20
R-SC40-PCO		R-SC40-PCO-16	Ø 16	100
		R-SC40-PCO-20	Ø 20	100
		R-SC40-PCO-25	Ø 25	90
		R-SC40-PCO-32	Ø 32	50
		R-SC40-PCO-40	Ø 40	35
R-SC40-TCS		R-SC40-TCS	5,5x17mm	100
R-SC40-TCD		R-SC40-TCD	5,5x17mm (x2)	90
R-SC40-PCD		R-SC40-PCD-16	Ø 16-19	60
		R-SC40-PCD-20	Ø 20-23	50
		R-SC40-PCD-25	Ø 25-28	30
R-SC40-PCS		R-SC40-PCS-16	Ø 16-17	100
		R-SC40-PCS-18	Ø 18-19	80
		R-SC40-PCS-20	Ø 20-21	80
		R-SC40-PCS-22	Ø 22-23	70
		R-SC40-PCS-25	Ø 25-26	60
		R-SC40-PCS-28	Ø 28-29	50
R-SC40-PCS-32	Ø 32-33	50		
R-SC40-CBS		R-SC40-CBS	76x7,5	40
R-SC40-CBD		R-SC40-CBD	76x7,5mm (x2)	20

THE SYSTEM CREATED TO REDUCE A WORKING TIME AND ADVANCE A SERIAL FASTENING COMFORT

- Guarantees **serial fixing** of the point in 0.2 seconds
- Provides **15 times faster** and therefore more cost effective installation relative to traditional wall plugs
- Improves **work comfort** due to dustless operation, low weight and a reduced threshold noise and slight recoil
- Plastic and metal installation brackets allow for the **efficient installation of cables and pipes** on ceilings, walls and floors

BASE MATERIALS

Concrete C20/25-C50/60, cracked concrete, solid concrete block, rolled steel structure



Press the tool against the fixture and base material. Wait a fraction of a second to let the gas and air create an ignitable mixture. Press the trigger to perform the fixing to the steel or concrete. Remove your finger from the trigger and retract the tool from the fixing point.

Skipping any of these steps will prevent you from performing the correct fixing.

RAWLPLUG Ltd
Skibo Drive
Thornliebank Industrial Estate
Glasgow G46 8JR

rawlinfo@rawlplug.co.uk
www.rawlplug.co.uk
tel: +44 (0) 141 6387 961

RAWLPLUG®

SC40

DIRECT FASTENING SYSTEM FOR CONCRETE AND STEEL

NEW Range of Accessories

Gas powered nailer SC40II / pins with fuel cells / installation clips



SPEED UP YOUR WORK IN COMFORT!

100 years 1919-2019 **RAWLPLUG®**
www.rawlplug.com



DIRECT FASTENING SYSTEM FOR CONCRETE AND STEEL SC40

Pins with fuel cells

Unique, **high energy Rawlplug gas mix** ensures obtaining the highest single energy shot, which allows nails to be nailed in the range of 15-40 mm in concrete and steel



Top class cleanliness propane-butane prevents formation of impurities in the machine and extends trouble-free operation of the nailer

Gas resistance to a **wide range of temperatures** from -5 °C to 35 °C allows you to extend the working season of installation work

Synthetic oil content ensures trouble-free machine work for long time



Ballistic point **increases performance** into the base material

Full round head for a secure fixing with the highest performance **achieved independently** of the base material and the type of fastened element



Plastic collation provides protection from deterioration by weather conditions or high humidity

SC40II gas powered nailer

Lithium-ion battery up to **8000 fixings per charge**

Fast charging **2 minutes + 200 mounts**

Improved **distribution mas, limits forearm overload** and provides work comfort

One of the **lowest weights** in the market

Stand-by mode after **10 minutes** of inactivity **saves battery power**

Dedicated barrel's **magnet holder** positions and keeps steel washers and clips during installation

New cleaning and maintenance mechanism extends nailer lifespan by **40%**



Tool-free comfort depth adjustment nail seating in 2 modes ensures **quick use**

Installation clips



R-SC40-PCR



R-SC40-PCO



R-SC40-HEX



R-SC40-PCD



R-SC40-PCS



R-SC40-CBD



R-SC40-CBS



R-SC40-TCD



R-SC40-TCS



R-SC40-MW-25



R-SC40-MCD



R-SC40-MCS

plastic

metal